




Idealgehäuse/Optimum Enclosures



Geschlossen/Sealed 26.4 Liter



Reflex/Vented 47.0 Liter
10 x 18 cm CP* (1x)

*Competition Port - Port-Abmessungen basieren auf der Verwendung eines HELIX Competition Ports
Port measures are based on the use of a HELIX Competition Port

Gleichstromwiderstand	Resistance	R_{dc} [in Ω]	3.2
Nennimpedanz	Impedance	Z_N [in Ω]	4
Resonanzfrequenz	Resonance Frequency	f_s [in Hz]	21.4
Belastbarkeit	Power Handling	RMS[in Watt]	350
Mechanische Güte	Mechanical Q	Q_{ms}	3.59
Elektrische Güte	Electrical Q	Q_{es}	0.33
Gesamtgüte	Total Q	Q_{ts}	0.30
Maximale Auslenkung	Xmax	Xmax[mm]	11.00
Dynamisch bewegte Masse	Moving Mass	m_d [in g]	174.9
Wirkungsgrad	Sensitivity	SPL [in dB]	87.3
Mechanischer Widerstand	Mechanical Resistance	R_{ms} [in Kg/s]	6.6
Nachgiebigkeit	Compliance	C_{ms} [in mm/N]	0.31
Antriebsfaktor	Force Factor	BL [in Tm]	15.1
Äquivalentvolumen	Equivalent Volume	V_{as} [in dm ³]	118.6